

light+building

Frankfurt am Main Hall 8.0
18. - 23.3.2018 Stand A41

To this day Comatec is renowned for its commitment to design new products. This year will be no exception and, before taking part in the Light+Building 2018, we will be pleased to inform you about all our latest news.

Power supply for trunking boxes OTQ range



*Discover this innovative connection technique
Much easier to install thanks to its quick connections
Safe and extremely quick installation (no extra tools
required) Long lifetime connection*

Versions: 5V/10W, 12V/12W 24V/12 W

Input voltage: 90-260VAC - 50/60 Hz
(195-260VAC – 50/60 Hz 12V Version)

Output voltage : 5V, 12 or 24 VDC

Service condition: continuous

Maximum ambient temperature:

50°C without Derating

Efficiency: > 80 % (230V)

No load input power: < 0,3 W

Safety and EMC Standards : EN60335, EN61558-1,

EN61000-4, EN55032/B

Power supply for Din Rail mounting 150 W PSH04 Range



*Do not hesitate to contact us, we will be pleased to
answer your questions concerning the*

new PSH power supplies

Input voltage: 185-265VAC / 50-60Hz

Output voltage: 24 VDC

Output power: 150 W

Maximum ambient temperature:

50°C without Derating

No load input power < 0,3W (conform to ERP)

Efficiency > 95% (230V)

Regular functioning with zero load

Protection class: II

Protection degree: IP20

Service condition: continuous

Safety Standards: EN60335, EN60950, EN61558

EMC Standards: EN55032/B, EN61000-4

4 TE case

High power - 36 W Power supply for trunking boxes ORH Range



Do not hesitate to contact us, we will be pleased to answer your questions concerning the new ORH power supplies.

Versions: 12VDC/36W and 24VDC/36W

Input voltage: 230VAC $\pm 15\%$ – 50/60 Hz

Service condition: continuous

Maximum ambient temperature:

50°C without Derating

Efficiency: > 87 % (230V)

No load input power: < 0,2 W

Protection degree: IP65

(when using specific connectors)

Safety and EMC Standards : EN60335, EN60950,

EN61558-1, EN55032/B, EN61000-4

Availability: as from March 2018 (12V Version) and as from May 2018 (24V Version)

EN60335 Power supply for din rail mounting PSH Range



New PSH-Models in 3 and 4 case (60 W and 100 W)

Versions: 12 and 24VDC / 60W

12 and 24VDC / 100W

Input voltage: 185-265VAC / 50-60Hz

Maximum ambient temperature:

50°C without Derating

No load input power < 0,3W (conform to ERP)

Efficiency > 95% (230V)

Regular functioning with zero load

Protection class: II

Protection degree: IP20

Service condition: continuous

Safety Standards: EN60335, EN60950, EN61558

EMC Standards: EN55032/B, EN61000-4



Comatec Hi-Tech Srl
Via Aldo Manca 98/M
06132 San Andrea delle Fratte
Perugia - Italy
Tel: +39 07 55 28 85 41
Fax: +39 07 55 28 79 46
e-mail: info@comatec.eu
www.comatec-hitech.com



light+building

Frankfurt am Main Hall 8.0
18. - 23.3.2018 Stand A41

We look forward to welcoming you from March 18th to 23rd, 2018, to introduce most widely our novelties!